



This safety data sheet is prepared in accordance with EU directive 91/155/EC amended by Directive 2001/58/EC



SAFETY DATA SHEET

Laminate spray for daily use

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Product name : Laminate spray for daily use
Product use : Removes light areas of dirt from your laminate floor in no time

Company/undertaking identification

Manufacturer : HG International b.v. **Telephone No.:** : +31 (0)36 54 94 700
Address : Damsluisweg 70 **Fax** : +31 (0)36 54 94 744
1332 EJ Almere **Internet:** : www.hginternational.com
Country : Netherlands
Importer : HG UK
Address : Unit 11 Grange Way Business Park Whitehall Road Industrial Estate
Uk Colchester Essex CO2 8HF
Telephone No.: : +44.1206.795.200
Fax : +44.1206.795.201
Country : United Kingdom (UK)

2. Composition/information on ingredients

Substance/preparation : Preparation

Ingredient name	CAS number	EC Number	%	Classification
United Kingdom (UK) propan-2-ol	67-63-0	200-661-7	0 - 1	F; R11 Xi; R36 R67

See section 16 for the full text of the R Phrases declared above

* Occupational Exposure Limit(s), if available, are listed in Section 8

3. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.

Additional Hazards : Not applicable

See section 11 for more detailed information on health effects and symptoms.

4. First aid measures

First aid measures

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.

Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.

Date of issue

14-10-2005.

Version

5.05

Page: 1/6

SAFETY DATA SHEET

Laminate spray for daily use

- Skin Contact** : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Obtain medical attention.
- Eye contact** : In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Get medical attention if irritation occurs.
- Notes to physician** : Not available.
- Specific treatments** : Not available.
- See section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

- Extinguishing media** : Use an extinguishing agent suitable for surrounding fires.
- Special exposure hazards** : No specific hazard.
Not available.
- Hazardous thermal decomposition products** : These products are carbon oxides (CO, CO₂).
- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

- Personal Precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Wash thoroughly after handling.
- Storage** : Keep container tightly closed. Keep container in a cool, well-ventilated area.
- Packaging materials**
- Recommended** : Use original container.
- Specific uses** : Not available.

8. Exposure controls/personal protection

Ingredient name

United Kingdom (UK)

propan-2-ol

Occupational exposure limits

EH40-WEL (United Kingdom (UK), 1/2005).

STEL: 1250 mg/m³ 15 minute(s). Form: All forms

STEL: 500 ppm 15 minute(s). Form: All forms

TWA: 999 mg/m³ 8 hour(s). Form: All forms

TWA: 400 ppm 8 hour(s). Form: All forms

Exposure controls

Date of issue

14-10-2005.

Version

5.05

Page: 2/6

SAFETY DATA SHEET

Laminate spray for daily use

Occupational exposure controls	: No special ventilation requirements.
Respiratory protection	: A respirator is not needed under normal and intended conditions of product use.
Hand protection	: Butyl rubber gloves. Permeation time \geq 8 hours: (5 mm)
Eye protection	: splash goggles
Skin protection	: Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits).

9. Physical and chemical properties

General information

Appearance	
Physical state	: Liquid.
Colour	: Clear Colourless.
Odour	: Perfumed

Important health, safety and environmental information

pH	: 8.5 (Conc. (% w/w): 100) [Basic.]
Melting point	: May start to solidify at 0°C (32°F) based on data for: Water. Weighted average: -0.9°C (30.4°F)
Boiling point	: The lowest known value is 82.5°C (180.5°F) (propan-2-ol). Weighted average: 99.82°C (211.7°F)
Flash point	: Closed cup: >100°C (212°F).
Explosive properties	: Not available.
Oxidising properties	: Not applicable
Relative density	: 0.997 g/cm ³ (20°C / 68°F)
Solubility	: Easily soluble in cold water, hot water, methanol, diethyl ether, acetone.
Evaporation rate (butyl acetate = 1)	: 1.7 (propan-2-ol) compared to Butyl acetate.

Other information

Auto-ignition temperature	: The lowest known value is 399°C (750.2°F) (propan-2-ol).
----------------------------------	--

10. Stability and reactivity

Stability	: The product is stable.
Conditions to Avoid	: Stable under recommended storage and handling conditions (see section 7). Keep away from heat, sparks and flame.
Materials to avoid	: Not considered to be reactive according to our database.
Hazardous Decomposition Products	: These products are carbon oxides (CO, CO ₂).

11. Toxicological information

Potential acute health effects

Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin Contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.

Acute toxicity

Date of issue

14-10-2005.

Version

5.05

Page: 3/6

SAFETY DATA SHEET

Laminate spray for daily use

<u>Ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
propan-2-ol	LD50	5045 mg/kg	Oral	Rat
	LD50	6410 mg/kg	Oral	Rabbit
	LD50	3600 mg/kg	Oral	Mouse
	LD50	12800 mg/kg	Dermal	Rabbit
	LD50	12800 mg/kg	Dermal	Rabbit
	LDLo	1537 mg/kg	Oral	Dog
	LDLo	3570 mg/kg	Oral	human
	LDLo	5272 mg/kg	Oral	man

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin : No known significant effects or critical hazards.

Target organs : Contains material which causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Other adverse effects : Not available.

12. Ecological information

Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
propan-2-ol	Pimephales promelas (EC50)	48 hour(s)	10000 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	>1400 mg/l
	Pimephales promelas (LC50)	96 hour(s)	6550 mg/l
	Pimephales promelas (LC50)	96 hour(s)	9640 mg/l
	Pimephales promelas (LC50)	96 hour(s)	10400 mg/l
	Pimephales promelas (LC50)	96 hour(s)	11130 mg/l

No known significant effects or critical hazards.

Other adverse effects

13. Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Waste classification : Not applicable.

: Not available.

Hazardous waste : To present knowledge of the supplier, this product is not regarded as hazardous waste as defined by EU Directive 91/689/EC.

Date of issue

14-10-2005.

Version

5.05

Page: 4/6

SAFETY DATA SHEET

Laminate spray for daily use

14. Transport information

International transport regulations

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional Information
ADR/RID Class	Not regulated.	-	-	-		-
ADN Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

15. Regulatory information

EU Regulations

- Risk Phrases** : This product is not classified according to the EU regulations.
- Safety Phrases** : S2- Keep out of the reach of children.
S46- If swallowed, seek medical advice immediately and show this container or label.
- Other EU regulations** : Not available.
- Product use** : Classification and labelling have been performed according to EU directives 67/548/EEC, 1999/45/EC, including amendments and the intended use.
- Consumer applications.
- Additional warning phrases** : Safety data sheet available for professional user on request.
- EC Statistical classification (Tariff Code)** : 32089091
- Ingredients identification information** : less than 5%: non-ionic surfactants, anionic surfactants, preservation agents: (ethylenedioxy) dimethanol, 1,3-bis(hydroxymethyl)urea, [2-(2-butoxyethoxy)ethoxy]methanol, 2-Bromo-2-nitropropane-1,3-diol, Methylchlorisothiazolinone, Methylisothiazolinone, perfumes

16. Other information

- Full text of R phrases referred to in sections 2 and 3 - United Kingdom (UK)** : R11- Highly flammable.
R36- Irritating to eyes.
R67- Vapours may cause drowsiness and dizziness.
- Full text of classifications referred to in sections 2 and 3 - United Kingdom (UK)** : F - Highly flammable
Xi - Irritant

History

- Date of printing** : 14-10-2005.
- Date of issue** : 14-10-2005.
- Version** : 5.05
- Verified by T. Rutgers.**

Notice to reader

Date of issue	Version	Page: 5/6
14-10-2005.	5.05	



This safety data sheet is prepared in accordance with EU directive 91/155/EC amended by Directive 2001/58/EC



SAFETY DATA SHEET

Laminate spray for daily use

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Version 5.05

Page: 6/6