



## SAFETY DATA SHEET

### Marble protector

#### 4. First aid measures

##### First aid measures

- Inhalation** : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.
- Ingestion** : If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed- can enter lungs and cause damage. Obtain medical attention.
- Skin Contact** : Wash with soap and water. Get medical attention if irritation develops.
- Eye contact** : In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Get medical attention if irritation occurs.
- Notes to physician** : Not available.
- Specific treatments** : Not available.

See section 11 for more detailed information on health effects and symptoms.

#### 5. Fire-fighting measures

- Extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub> extinguisher or spray.
- Special exposure hazards** : Flammable liquid and vapour. Vapour may cause flash fire. Vapours may accumulate in low or confined areas, travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.  
Not available.
- Hazardous thermal decomposition products** : These products are carbon oxides (CO, CO<sub>2</sub>).
- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### 6. Accidental release measures

- Personal Precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

#### 7. Handling and storage

- Handling** : Aspiration hazard if swallowed- can enter lungs and cause damage. Do not ingest. If ingested do not induce vomiting. Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Avoid contact of spilled material and runoff with soil and surface waterways. Wash thoroughly after handling.

## SAFETY DATA SHEET

### Marble protector

<b>Storage</b>	: Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
<b>Packaging materials</b>	
<b>Recommended</b>	: Use original container.
<b>Specific uses</b>	: Not available.

## 8. Exposure controls/personal protection

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
<u>United Kingdom (UK)</u>	
Xylene	<b>EH40-WEL (United Kingdom (UK), 1/2005). Skin</b> STEL: 441 mg/m <sup>3</sup> 15 minute(s). Form: All forms STEL: 100 ppm 15 minute(s). Form: All forms TWA: 220 mg/m <sup>3</sup> 8 hour(s). Form: All forms TWA: 50 ppm 8 hour(s). Form: All forms

#### Exposure controls

**Occupational exposure controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.

**Respiratory protection** : Wear appropriate respirator when ventilation is inadequate. Ventilation is normally required when handling or using this product.

**Hand protection** : Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
 >8 hour(s) (breakthrough time): polyvinyl alcohol (PVA)

**Eye protection** : safety glasses with side shields

**Skin protection** : Work uniform or laboratory coat.

## 9. Physical and chemical properties

#### General information

##### Appearance

**Physical state** : Liquid.

**Colour** : Colourless. Clear

**Odour** : Hydrocarbon. (Slight.)

#### Important health, safety and environmental information

**pH** : Not applicable.

**Melting point** : May start to solidify at <-20°C (-4°F) based on data for: Naphtha (petroleum), hydrodesulfurized heavy. Weighted average: -20.14°C (-4.3°F)

**Boiling point** : 157 to 198°C (314.6 to 388.4°F)

**Flash point** : Closed cup: 45°C (113°F). (Pensky-Martens.)

**Flammability (solid, gas)** : Not applicable.

**Explosive properties** : Not available.

**Explosion Limits** : Lower: 0.6% Upper: 6.5%

**Oxidising properties** : Not available.

**Relative density** : 0.8 g/cm<sup>3</sup> (20°C / 68°F)

**Solubility** : Insoluble in cold water, hot water.

<b>Date of issue</b>	<b>Version</b>	<b>Page:</b> 3/7
2-11-2005.	5.04	

## SAFETY DATA SHEET

### Marble protector

Evaporation rate (butyl acetate = 1) : 0.77 (Xylene) compared to Butyl acetate.

#### Other information

Auto-ignition temperature : 210°C (410°F)

### 10. Stability and reactivity

- Stability** : The product is stable.
- Conditions to Avoid** : Stable under recommended storage and handling conditions (see section 7). Keep away from heat, sparks and flame.
- Materials to avoid** : Extremely reactive or incompatible with oxidising agents, acids.
- Hazardous Decomposition Products** : These products are carbon oxides (CO, CO<sub>2</sub>).

### 11. Toxicological information

#### Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : Aspiration hazard if swallowed- can enter lungs and cause damage.
- Skin Contact** : Slightly irritating to the skin.
- Eye contact** : No known significant effects or critical hazards.

#### Acute toxicity

<u>Inгредиент name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Naphtha (petroleum), hydrodesulfurized heavy	LD50	>5000 mg/kg	Oral	Rat
	LD50	>3000 mg/kg	Dermal	Rabbit
Xylene	LD50	4300 mg/kg	Oral	Rat
	LD50	2119 mg/kg	Oral	Mouse
	LD50	4300 mg/kg	Oral	Mammal
	LD50	>1700 mg/kg	Dermal	Rabbit
	LD50	1700 mg/kg	Dermal	Rabbit
	LDLo	50 mg/kg	Oral	human

- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin** : No known significant effects or critical hazards.
- Target organs** : Contains material which causes damage to the following organs: blood, kidneys, liver, gastrointestinal tract, skin, central nervous system (CNS), eye, lens or cornea.

- Other adverse effects** : Not available.

## SAFETY DATA SHEET

### Marble protector

#### 12. Ecological information

##### Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Naphtha (petroleum), hydrodesulfurized heavy	Trout (LC50)	96 hour(s)	41.4 mg/l
	Shrimp (IC50)	96 hour(s)	4.3 mg/l
Xylene	Oncorhynchus mykiss (LC50)	96 hour(s)	3.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	8.2 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	8.6 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	12 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	13.3 mg/l
	Pimephales promelas (LC50)	96 hour(s)	13.4 mg/l

Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

##### Other adverse effects

#### 13. Disposal considerations



**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

**Waste classification** : 200113

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste

#### 14. Transport information

##### International transport regulations

<u>Regulatory information</u>	<u>UN number</u>	<u>Proper shipping name</u>	<u>Class</u>	<u>Packing group</u>	<u>Label</u>	<u>Additional Information</u>
<b>ADR/RID Class</b>	1300	UN 1300, "dangerous goods in limited quantities of class 3", III, ADR (Naphtha (petroleum), hydrodesulfurized heavy)	3	III		<b>Hazard identification number</b> 30  <b>Reportable quantity</b> 45  <b>Remarks</b> Dangerous goods in limited quantities Keep in frostfree area
<b>ADN Class</b>	1300	UN 1300, "dangerous goods in limited quantities of class 3", III, ADN (Naphtha (petroleum), hydrodesulfurized heavy)	3	III		<b>RQ (Reportable quantity) ADN</b> 45  <b>Remarks</b> Dangerous goods in limited quantities Keep in frostfree area

##### Date of issue

2-11-2005.



**Version**

5.04

**Page: 5/7**

## SAFETY DATA SHEET

### Marble protector

<b>IMDG Class</b>	1300	"dangerous goods in limited quantities of class 3" (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant (Naphtha (petroleum), hydrodesulfurized heavy)	3	III		<b>Emergency schedules (EmS)</b> F-E, S-E  <b>Marine pollutant</b> Marine pollutant (P)  <b>Reportable quantity</b> 45  <b>Remarks</b> Dangerous goods in limited quantities Keep in frostfree area
<b>IATA-DGR Class</b>	1300	"dangerous goods in limited quantities of class 3" UN 1300, (Naphtha (petroleum), hydrodesulfurized heavy)	3	III		<b>Remarks</b> Keep in frostfree area

## 15. Regulatory information

### EU Regulations

**Hazard symbol(s)**



Harmful, Dangerous for the environment.

**Risk Phrases**

- : R10- Flammable.
- R65- Harmful: may cause lung damage if swallowed.
- R66- Repeated exposure may cause skin dryness or cracking.
- R67- Vapours may cause drowsiness and dizziness.
- R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety Phrases**

- : S2- Keep out of the reach of children.
- S24- Avoid contact with skin.
- S29/56- Do not empty into drains, dispose of this material and its container to hazardous or special waste collection point.
- S43- In case of fire, use Powder sand CO2.
- S46- If swallowed, seek medical advice immediately and show this container or label.
- S62- If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Other EU regulations**

: Not available.

**Product use**

- : Classification and labelling have been performed according to EU directives 67/548/EEC, 1999/45/EC, including amendments and the intended use.
- Consumer applications.

### Other EU regulations

**Child protection**

: Yes, applicable.

**Tactile warning of danger**

: Yes, applicable.

**EC Statistical classification (Tariff Code)**

: 32089091

**Date of issue**

2-11-2005.

**Version**

5.04

## SAFETY DATA SHEET

### Marble protector

**Ingredients identification information** : 30% and more: aliphatic hydrocarbons.5% or over but less than 15%:aromatic hydrocarbons

#### 16. Other information

**Full text of R phrases referred to in sections 2 and 3 - United Kingdom (UK)** : R10- Flammable.  
R20/21- Harmful by inhalation and in contact with skin.  
R65- Harmful: may cause lung damage if swallowed.  
R38- Irritating to skin.  
R66- Repeated exposure may cause skin dryness or cracking.  
R67- Vapours may cause drowsiness and dizziness.  
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications referred to in sections 2 and 3 - United Kingdom (UK)** : Xn - Harmful  
Xi - Irritant  
N - Dangerous for the environment.

#### History

**Date of printing** : 2-11-2005.

**Date of issue** : 2-11-2005.

**Version** : 5.04

**Verified by T. Rutgers.**

#### Notice to reader

*To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

**Version** 5.04

**Page: 7/7**