



Hotspot Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 [www.rustins.ltd/hotspot](http://www.rustins.ltd/hotspot)

November 2020

## PRODUCT DATA SHEET

<b>Product</b>	<b>Brick and Stone Sealer</b>
<b>Type</b>	Solvent-based combination of resins, oils and special compounds.
<b>Intended Use</b>	Formulated for sealing and protecting natural brick and stone or fireplace surrounds. The sealer allows brick and stones to breathe. It will make the surface strongly repellent to oil, water dirt and dust.
<b>Special Features</b>	It will enhance the natural beauty of the brick and stone. Depending on the nature of the brick and stone it can slightly deepen the colour.
<b>Preparation</b>	Ensure the surface to be treated is cool, it is very important the surface is thoroughly cleaned of dust with a vacuum to remove all loose dust. For best results, use Fireplace Cleaner to remove any stains. Remove screens, fixtures, etc. and protect floors and carpets. Working area to be well ventilated, wear protective gloves. It is recommended to test on an inconspicuous area to test for suitability prior to complete application.
<b>Application</b>	Pour Brick and Stone Cleaner into a clear tray or saucer and apply by brush or lint-free cloth. Bear in mind that application by brush may cause streaking.
<b>Coats</b>	One coat should be sufficient for indoor surface coverage but for greater protection outdoors, apply 2 or 3 additional coats. Ensure that thorough cleaning is achieved again between each coat.
<b>Drying Time</b>	Leave to dry for 2-4 hours before use but where possible, leave to dry overnight: it is then heat resistant to 90°C. Allow 2-4 hours before use.
<b>Re-coating Time</b>	Leave to dry for 2-4 hours between coats.
<b>Application Temp.</b>	15 – 25 degrees Centigrade.
<b>Coverage</b>	Depending on the porosity of the stone, approximately 5-8m <sup>2</sup> per 500ml.
<b>Maintenance</b>	As required.
<b>Compatibility</b>	For use on clean brick and stone. Not suited to reconstituted stone.
<b>Settlement</b>	Stir well before use.
<b>Shelf-life/Storage</b>	2 years if stored unopened in a cool, dry place.
<b>Hazards</b>	Flammable, keep out of reach of children. For further product safety details download SDS from <a href="http://www.rustinsltd/hotspot">www.rustinsltd/hotspot</a> or contact directly.
<b>Clean-Up</b>	Clean up with xylene thinners.
<b>Sizes</b>	500ml bottle