SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : LIBERON - ANTI-SLIP COATING - 1L Product code : 101767

1.2. Relevant identified uses of the substance or mixture and uses advised against

Varnish

1.3. Details of the supplier of the safety data sheet

Registered company name : LIBERON Ltd Address : .Mountfield Industrial Estate KENT TN28 8XU NEW ROMNEY GB Telephone : + (44) 1797 367 555. Fax: + (44) 1797 367 575. Telex: . fds.produits@v33.com www.liberon.co.uk

1.4. Emergency telephone number : .

Association/Organisation : .

Other emergency numbers

UK/NI: 111 - Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Republic of Ireland : +353 (0)1 809 2166 - Emergency medical information: 8am-10pm (seven days) contact NPIC, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :	
EUH208	Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.
EUH208	Contains REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H
	-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.
Precautionary statements - G	eneral :
P102	Keep out of reach of children.
Precautionary statements - Pr	revention :
P271	Use only outdoors or in a well-ventilated area.
Precautionary statements - Di	isposal :
P501	Dispose of contents/container to a waste collection center (contact the local authority)

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: Z127		[1]	0 <= x % < 2.5
CAS: 34590-94-8			
EC: 252-104-2			
REACH: 01-2119450011-60			
DIPROPYLENE GLYCOL MONOMETHYL			

SAFETY DATA SHEET (REG	ULATION (EC) n° 1907/2006 - REACH)
LIBERON - ANTI-SLIP COAT	NG - 1L - 101767

ERON - ANTI-SLIP COATING - IL - 101707			
ETHER			
INDEX: 613_088_006B	GHS06, GHS05, GHS09		0 <= x % < 0.05
CAS: 2634-33-5	Dgr		
EC: 220-120-9	Acute Tox. 4, H302		
	Skin Irrit. 2, H315		
1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1, H317		
	Eye Dam. 1, H318		
	Acute Tox. 2, H330		
	Aquatic Chronic 2, H411		
	Aquatic Acute 1, H400		
	M Acute = 1		
		[4]	0.1
INDEX: Z117	GHS06, GHS05, GHS09	[1]	0 <= x % < 0.0015
CAS: 55965-84-9	Dgr		
REACH: 01-2120764691-48	Acute Tox. 3, H301		
	Acute Tox. 2, H310		
REACTION MASS OF:	Skin Corr. 1C, H314		
5-CHLORO-2-METHYL-4-ISOTHIAZOLI	Skin Sens. 1A, H317		
N-3-ONE AND 2-METHYL-2H	Eye Dam. 1, H318		
-ISOTHIAZOL-3-ONE (3:1)	Acute Tox. 2, H330		
	Aquatic Acute 1, H400		
	M Acute = 100		
	Aquatic Chronic 1, H410		
	M Chronic = 100		

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) LIBERON - ANTI-SLIP COATING - 1L - 101767

Do not breathe in smoke.

- In the event of a fire, the following may be formed :
- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Do not allow to freeze

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :	
34590-94-8	308	50	-	-	Peau	
- Germany - A	GW (BAuA - TRGS 90	00, 08/08/2019) :				
CAS	VME :	VME :	Excess	Notes		
34590-94-8		50 ppm		1(I)		
		310 mg/m ³				
- France (INRS	6 - ED984 / 2020-154	6):				
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
34590-94-8	50	308	-	-	*	84

- Switzerland (SUVAPRO 2019) :

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) LIBERON - ANTI-SLIP COATING - 1L - 101767

CAS	VME	VLE	Valeur plafond	Notations		
34590-94-8	100 ppm	150 ppm		Skin		
55965-84-9	0.2 ppm	0.4 mg/m ³				
- UK / WEL	(Workplace exposur	e limits, EH40/2005,	, Fourth Edition 2020) :			
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
34590-94-8	50 ppm			Sk		
	308 mg/m ³					
8.2. Exposure	e controls					
Personal pro	tection measures, s	such as personal p	rotective equipment			
Use person	al protective equipme	ent that is clean and	has been properly mair	ntained.		
•	• • • •		e, away from the work a			
•	• • • •	•	wash contaminated clot		. Ensure that there is	adequate ventilation

especially in confined areas. - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Fluid liquid.
Important health, safety and environmental informati	ion
рН :	8.50 .
	Slightly basic.
Boiling point/boiling range :	Not relevant.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	>1
Water solubility :	Dilutable.
Melting point/melting range :	Not relevant.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid : - frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity :

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9) LD50 > 2000 mg/kg Oral route :

Dermal route :

LD50 > 5000 mg/kg

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12

12.1.1. Substances	
REACTION MASS OF: 5-CHLORO-2-M	IETHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)
Fish toxicity :	LC50 = 0.22 mg/l
	Factor M = 1
	Species : Oncorhynchus mykiss
	Duration of exposure : 96 h
	OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 = 0.1 mg/l
	Factor M = 10
	Species : Daphnia magna
	Duration of exposure : 48 h
	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 = 0.0052 mg/l
	Factor M = 100
	Species : Skeletonema costatum
	Duration of exposure : 48 h
	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50 mg/l
	Factor M = 10
	Species : Skeletonema costatum
	Duration of exposure : 48 h
	ISO 10253 (Water quality - Marine Algal Growth Inhibition Test with
	Skeletonema costatum and Phaeodactylum tricornutum)
	NOEC = 0.00064 mg/l
	Factor M = 100
	Species : Skeletonema costatum
	Duration of exposure : 48 h
	ISO 10253 (Water quality - Marine Algal Growth Inhibition Test with
	Skeletonema costatum and Phaeodactylum tricornutum)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9) Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5) Biodegradability :

Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

 REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

 Octanol/water partition coefficient :
 log Koe <= 0.71</td>

 OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

Bioaccumulation :

BCF = 3.16

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

14.2. UN proper shipping name

- -
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- -
- 14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/669 (ATP 11)
- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations :

STEL : Short-term exposure limit

- TWA : Time Weighted Averages
- TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.