



Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830
Issue date: 10/23/2020 Revision date: 6/28/2022 Supersedes version of: 6/28/2022 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Bonda Hardener Tube (White)
Product code : BONO2300
Type of product : Paste
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use
Use of the substance/mixture : Catalyst
Function or use category : Oxidising agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Bondaglass Voss Ltd
Rustins Ltd
Waterloo road
NW2 7TX London
United Kingdom
T +44 (0)208 450 4666 - F +44 (0)208 452 2008
rustins@rustins.co.uk - rustins.ltd

Distributor

Excellence Ltd
43 Grange Parade,
Unit 43 Baldoyle Industrial Estate,
D13 Y860 Dublin
Ireland
T 00353 (0)1 8323300 - F 00353 (0)1 8323584
Orders@excellence.ie - www.excellence.ie

1.4. Emergency telephone number

Emergency number : +44 (0)208 450 4666
OFFICE HOURS ONLY MON. - FRI. 08:00 - 16:30

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Organic Peroxides, Type C H242
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Acute Hazard, Category 1 H400
Hazardous to the aquatic environment – Chronic Hazard, Category 1 H410
Full text of H- and EUH-statements: see section 16

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Adverse physicochemical, human health and environmental effects

Heating may cause a fire. May cause an allergic skin reaction. Causes serious eye irritation. Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS09

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H242 - Heating may cause a fire.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)
: P102 - Keep out of reach of children.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dibenzoyl peroxide; benzoyl peroxide	CAS-No.: 94-36-0 EC-No.: 202-327-6 EC Index-No.: 617-008-00-0	45 – 55	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317
ethanediol; ethylene glycol	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1	0.1 – 15	Acute Tox. 4 (Oral), H302

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Heating may cause a fire.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store away from other materials. Protect from sunlight. Keep only in original container. Keep cool. Store in a well-ventilated place.
Incompatible materials	: combustible materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Bonda Hardener Tube (White)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA [ppm]	20 ppm
IOEL STEL	104 mg/m ³
IOEL STEL [ppm]	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Peroxyde de dibenzoyl # Dibenzoylperoxide
OEL TWA	5 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	D: la mention "D" signifie que la r�sorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette r�sorption peut se faire tant par contact direct que par pr�sence de l'agent dans l'air, M: la mention "M" indique que lors d'une exposition sup�rieure � la valeur limite, des irritations apparaissent ou un danger d'intoxication aigu� existe. Le proc�d� de travail doit �tre con�u de telle fa�on que l'exposition ne d�passe jamais la valeur limite. Lors des mesurages, la p�riode d'�chantillonnage doit �tre aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le r�sultat des mesurages est calcul� en fonction de la p�riode d'�chantillonnage. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht, M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkproc�d� moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arr�t� royal 11/05/2021
Croatia - Occupational Exposure Limits	
Local name	Dibenzoil peroksid; benzoil peroksid
GVI (OEL TWA) [1]	5 mg/m ³
GVI (OEL TWA) [2]	20 ppm

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Bonda Hardener Tube (White)	
KGVI (OEL STEL)	104 mg/m ³
KGVI (OEL STEL) [ppm]	40 ppm
Remark	Alergen koža (tvar koja može izazvati alergijsku reakciju na koži (H317))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Cyprus - Occupational Exposure Limits	
Local name	Αιθυλενογλυκόλη
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	δέρμα
Regulatory reference	Κανονισμοί του 2007 (Κ.Δ.Π. 295/2007)
France - Occupational Exposure Limits	
Local name	Ethylèneglycol (vapeur)
VME (OEL TWA)	52 mg/m ³
VME (OEL TWA) [ppm]	20 ppm
VLE (OEL C/STEL)	104 mg/m ³
VLE (OEL C/STEL) [ppm]	40 ppm
Remark	Valeurs règlementaires indicatives; risque de pénétration percutanée
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	5 mg/m ³ (E)
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	1(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Ireland - Occupational Exposure Limits	
Local name	Dibenzoyl peroxide [Benzoyl peroxide]
OEL TWA [1]	5 mg/m ³
OEL TWA [2]	20 ppm vapour

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Bonda Hardener Tube (White)	
OEL STEL	104 mg/m ³ vapour
OEL STEL [ppm]	40 ppm vapour
Remark	Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	Etilen glicol
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Etilēnglikols, (1,2-etāndiols)
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Luxembourg - Occupational Exposure Limits	
Local name	Éthylène-glycol
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Bonda Hardener Tube (White)	
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
Portugal - Occupational Exposure Limits	
Local name	Etilenoglicol
OEL C [ppm]	100 ppm H (Apenas aerossol)
Remark	A4 (Agente não classificável como carcinogénico no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Etilenglicol/Etandiol
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Serbia - Occupational Exposure Limits	
Local name	етилен гликол; етандиол
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	EY* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа); К – напомена да хемијска материја може штетно деловати на кожу
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09, 117/17 и 107/21)
Slovenia - Occupational Exposure Limits	
Local name	dibenzoilperoksid (benzoilperoksid)
OEL TWA	5 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	5 mg/m ³
OEL STEL [ppm]	40 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Peróxido de benzoilo
VLA-ED (OEL TWA) [1]	5 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
VLA-EC (OEL STEL)	104 mg/m ³

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Bonda Hardener Tube (White)	
VLA-EC (OEL STEL) [ppm]	40 ppm
Remark	Sen (Sensibilizante).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
North Macedonia - Occupational Exposure Limits	
Local name	дибензоилпероксид (бензоилпероксид)
OEL TWA	5 mg/m ³ (l) инхалабилна фракција – дел на вкупно суспендирани материи, кои работникот ги вдишува
OEL TWA [ppm]	20 ppm
KTV	1
Short time value [mg/m ³]	5 mg/m ³
Short time value [ppm]	20 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Turkey - Occupational Exposure Limits	
Local name	Etilen glikol
OEL TWA	52 mg/m ³
OEL TWA [ppm]	20 ppm
OEL STEL	104 mg/m ³
OEL STEL [ppm]	40 ppm
Comments	Deri
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Bonda Hardener Tube (White)	
DNEL/DMEL (Workers)	
Long-term - local effects, dermal	≈ 0.034 mg/kg dwt
Long-term - systemic effects, inhalation	≈ 13.3 mg/kg bw/day
Long-term - local effects, inhalation	≈ 39 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	≈ 2 mg/kg bw/day

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Bonda Hardener Tube (White)	
PNEC (Water)	
PNEC aqua (freshwater)	≈ 0.000002 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	≈ 0.00127 µg/kg dw
PNEC sediment (marine water)	≈ 0.00127 µg/kg dw

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: white.
Odour	: Characteristic odour.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 0 °C

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: 0 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: SADR =50
Flammability (solid, gas)	: Heating may cause a fire.
Vapour pressure	: ≈ 23 hPa at 20degC
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.15 – 1.25 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating may cause a fire.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Combustible materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Bonda Hardener Tube (White)	
LD50 oral	≈ 2000 mg/kg
LC50 Inhalation - Rat	≈ 24.3 mg/l

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Bonda Hardener Tube (White)

Viscosity, kinematic	Not applicable
----------------------	----------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Not rapidly degradable	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information





In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3108	UN 3108	Not regulated	UN 3108	UN 3108
14.2. UN proper shipping name				
ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzyl Peroxide)	ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzyl Peroxide)	Not regulated	ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzyl Peroxide)	ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzyl Peroxide)

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
Transport document description				
UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzoyl Peroxide), 5.2, (D), ENVIRONMENTALLY HAZARDOUS	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzoyl Peroxide), 5.2, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	Not regulated	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzoyl Peroxide), 5.2, ENVIRONMENTALLY HAZARDOUS	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (Contains: Dinebenzoyl Peroxide), 5.2, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
5.2	5.2	Not regulated	5.2	5.2
		Not regulated		
14.4. Packing group				
Not applicable	Not applicable	Not regulated	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Not regulated	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: P1
Special provisions (ADR)	: 122, 274
Limited quantities (ADR)	: 500g
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P520
Mixed packing provisions (ADR)	: MP4
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V1
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV15, CV22, CV24
Tunnel restriction code (ADR)	: D
EAC code	: 1W

Transport by sea

Special provisions (IMDG)	: 122, 274
Limited quantities (IMDG)	: 500 g
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P520
EmS-No. (Fire)	: F-J
EmS-No. (Spillage)	: S-R
Stowage category (IMDG)	: D
Stowage and handling (IMDG)	: SW1
Segregation (IMDG)	: SG35, SG36, SG72
Properties and observations (IMDG)	: Decomposes at elevated temperatures or in a fire. Burns vigorously. Insoluble in water. Contact with the eyes and skin should be avoided. May evolve irritant or toxic fumes.

Air transport

Not regulated

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Inland waterway transport

Classification code (ADN)	: P1
Special provisions (ADN)	: 122, 274
Limited quantities (ADN)	: 500 g
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: P1
Special provisions (RID)	: 122, 274
Limited quantities (RID)	: 500g
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P520
Mixed packing provisions (RID)	: MP4
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W7
Special provisions for carriage - Loading, unloading and handling (RID)	: CW22, CW24, CW29
Colis express (express parcels) (RID)	: CE10
Hazard identification number (RID)	: 539

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Organic solvent

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamide; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG) Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Netherlands

ABM category	: A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Class for fire hazard	: Class I-1
Store unit	: 1 liter
Classification remarks	: F <Org. Perox. C>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK)	: LK 5 - Oxidizing materials
--------------------	------------------------------

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

Bonda Hardener Tube (White)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Abbreviations and acronyms:	
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H241	Heating may cause a fire or explosion.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Org. Perox. B	Organic Peroxides, Type B
Skin Sens. 1	Skin sensitisation, Category 1

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.