

# **MOTIP Chewing Gum Freezer**

Ord.-no.: 090402



## **Quality & properties**

- Briefly decreases the temperature to -40°C
- Directed jetspray
- Very effective
- User-friendly

# **Technical Information**

Remove chewing gum from the upholstery of your car with MOTIP Chewing Gum Freezer. Effective tool for removing chewing gum from carpets, upholstery and pavement. Chewing gum freezer briefly decreases the temperature to - 40°C. MOTIP Chewing Gum Freezer is user-friendly and has a directed jet-spray.

# Physical & chemical data

- Base: Aliphatic hydrocarbons
- Colourname: no colour
- Smell: Characteristic
- Surfaces: Pavement, Clothing, Upholstery, Carpets
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,9
- Vapour pressure: 3500/20 bar
- Relative density: 0.559 g/ml
- Storage stability: 10 y
- Content: 500 ML

## How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Distance to the surface to be treated approximately 5 centimetre.
- · Before use, test the compatibility of the surface
- Spray the surface to be treated by repeatedly, briefly pressing the nozzle, till the chewing gum is completely frozen.
- As a result of the fierce decrease in temperature, the chewing gum can be removed. When required, the remaining adhesives can be removed with benzine.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 - This release replaces all eventually earlier issued versions.