



SAFETY DATA SHEET
PROFESSIONAL WOOD FILLER -TWO PART

Page: 1

Compilation date: 23/03/2017

Revision date: 03/01/2020

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROFESSIONAL WOOD FILLER -TWO PART

Product code: WOPN/WOPW

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd
Waterloo Road
Cricklewood
London
NW2 7TX
United Kingdom
Tel: +44 (0)208 450 4666
Fax: +44 (0)208 452 2008
Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.
H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.
P337+P313: If eye irritation persists: Get medical advice/attention.
P280: Wear eye protection and protective gloves.

[cont...]

SAFETY DATA SHEET

PROFESSIONAL WOOD FILLER -TWO PART

Page: 2

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

2.3. Other hazards

Other hazards: Flammable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

STYRENE

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|--|---------|
| 202-851-5 | 100-42-5 | - | Flam. Liq. 3: H226; Repr. 2: H361d; Acute Tox. 4: H332; STOT RE 1: H372; Skin Irrit. 2: H315; Eye Irrit. 2: H319 | 30.000% |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol or polymer foam.

[cont...]

SAFETY DATA SHEET
PROFESSIONAL WOOD FILLER -TWO PART

Page: 3

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Harmful. Flammable. Forms explosive air-vapour mixture. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Earth any equipment used in handling. Smoking is forbidden. Use non-sparking tools. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| | | | | |

[cont...]

SAFETY DATA SHEET
PROFESSIONAL WOOD FILLER -TWO PART

Page: 4

| | | | | |
|----|----------|-----------|---|---|
| UK | 430 m/m3 | 1080mg/m3 | - | - |
|----|----------|-----------|---|---|

Hazardous ingredients:

STYRENE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 430 mg/m3 | 1080 mg/m3 | - | - |

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus must be available in case of emergency.

Hand protection: PVC gloves. Nitrile gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Variable

Odour: Characteristic odour

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Boiling point/range°C: 145

Melting point/range°C: No data available.

Flammability limits %: lower: 1.1

upper: 6.1

Flash point°C: 32

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: 490

Vapour pressure: No data available.

Relative density: 1.1

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

[cont...]

SAFETY DATA SHEET
PROFESSIONAL WOOD FILLER -TWO PART

Page: 5

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. May polymerise on exposure to light.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.
Polymerisation may occur on exposure to conditions or materials listed below.
Polymerisation may generate enough heat and gases for fires/explosions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

STYRENE

| | | | | |
|-----|-----|------|------|-------|
| IVN | MUS | LD50 | 90 | mg/kg |
| ORL | MUS | LD50 | 316 | mg/kg |
| ORL | RAT | LD50 | 2650 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |
| Serious eye damage/irritation | OPT | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur.

[cont...]

SAFETY DATA SHEET
PROFESSIONAL WOOD FILLER -TWO PART

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Serious bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Deposit into or on to land (e.g. landfill, etc.)

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3269

14.2. UN proper shipping name

Shipping name: POLYESTER RESIN KIT (STYRENE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: E

[cont...]

SAFETY DATA SHEET
PROFESSIONAL WOOD FILLER -TWO PART

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs through prolonged or repeated exposure.

Legal disclaimer: Even after washing the rags must never be crumpled into a ball but spread out and disposed of. Use synthetic fibre cloths where possible as natural fibres, especially cotton, increase the chances of spontaneous combustion. This data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.