

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

March 2018 PRODUCT DATA SHEET	
Product	Tung Oil.
Туре	Pure Tung Oil.
Intended Use	Suitable for use on all types of interior timber.
Special Features	Has good penetration into all types of timber and its special properties make it highly resistant to water and alcohol and food stuffs. Conforms to Plastic Materials and Articles in contact with Food (England) regulations 2008.
Preparation	The surface must be clean, bare and sanded smooth and free of all traces of wax. Pure Tung Oil will bring out the natural colour of wood but if required the colour of the wood may be changed using Rustins Wood Dye. Always carry out test on a small area to assess the colour of the oil. If natural open-grain is not required then use Rustins Grain Filler before oiling.
Application	Using a clean soft cloth or brush apply liberally and allow the oil to penetrate for 20 minutes. Wipe of the excess with a clean soft cloth. The first coat of Rustins Pure Tung Oil can be diluted with 40% white spirit which will further assist penetration into the timber. Do not dilute subsequent coats. Under warm and dry conditions the product should be allowed to dry for 24 hours before further coats are applied. New or bare wood should be oiled 3 times initially but more coats can be applied for extra protection. The oiled surface should be allowed to cure for a few days before use.
Coats	Two coats are recommended.
Drying Time	More than 24 hrs in good conditions.
Re-coating Time	A minimum of 24 hrs in good conditions.
Application Temp.	Ideally 15-25° C. Do not use below 10°C or in conditions of high humidity.
Coverage	13 sq. metres per litre per coat
Maintenance	Re-application is recommended annually to keep surfaces in good condition. When applying to previously oiled wood the surface should be first cleaned and any wax removed with white spirit or Rustins Surface Cleaner. If the product is to be applied to a previously coated surface, then carry out a small test for compatibility.
Compatibility	Tung Oil may be used over the following Rustin's products: Wood Dye, Grainfiller, and Woodfiller.
Settlement	Shake well before use.
Shelf-life/Storage	Many years if stored in original, tightly closed container in cool dry conditions.
Hazards	Keep out of reach of children. Avoid contact with skin and eyes. No Smoking. A full Health & Safety Data Sheet is available upon request or on Rustins Web Site.
Clean-Up	Use White Spirit or Rustin's Brush Cleaner whilst still wet. If dried on, clean equipment and brushes with Rustin's Brush Restorer.