

Expert finishes for wood and metal

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

November 2012

PRODUCT DATA SHEET

Product	Small Job Quick Drying Primer & Undercoat				
Туре	Formulated with water borne acrylic emulsion, pigments and extenders to provide excellent opacity. Available in matt white and matt grey.				
Intended Use	As a primer for use on bare wood, hardboard, MDF, plaster, brickwork and cement. (Not for priming metals). Can also be used as an undercoat over existing wood and metal primers and over existing paints. For interior and exterior use.				
Special Features	Quick drying. Excellent covering power. Low odour. Clean brushes in water. One coat is usually sufficient to completely cover previous paints and provides the base for new applications.				
Preparation	Surfaces to be coated must be clean, dry and free from wax, grease and contaminants. When priming bare wood, knots must be sealed with Rustin's Knotting . Fill holes and cracks with Rustin's Wood Filler after priming. As an undercoat over existing paint, the surface must be cleaned and lightly sanded to provide a key before application.				
Application	Apply liberally and evenly with a synthetic fibre brush or roller. For brush application, if necessary, the primer coat may be thinned by mixing 5 parts with 1 part water. Do not thin when applying as undercoat.				
Coats	A minimum of 2 coats are required.				
Drying Time	Touch dry within 30 minutes, depending on temperature and humidity.				
Re-coating Time	2 hours minimum, depending on temperature and humidity.				
Application Temp.	Ideally 15-25°C. Do not use below 10°C or in conditions of high humidity.				
Coverage	Approximately 13 sq.m per litre, per coat, depending on the absorbency of the surface.				
Maintenance	N/A				
Compatibility	Compatible with many paint products, such as Rustin's White Gloss Paint and Rustin's Quick-Drying Radiator Enamel. Not for use as a metal primer. Metals must be primed using Rustin's Red Oxide Metal Primer.				
Settlement	STIR WELL BEFORE USE. Ensure any sediment is thoroughly mixed in.				
Shelf-life/Storage	Many years in a cool, dry place if stored in original, tightly closed container. Do not store below 5°C. Protect from frost and extremes of temperature.				
Hazards	Non-flammable. Avoid contact with eyes and skin. Eyes and skin should be rinsed immediately if contact occurs with plenty of water. Seek medical attention. Keep container tightly closed and out of reach of children. A full Health and Safety Data Sheet is Available on request or on www.rustins.co.uk				
Clean-Up	Clean brushes and hands immediately after use with water. If dried on, clean equipment and brushes with Rustin's Brush Restorer .				
Sizes	250ml				