

CELLULOSE THINNERS

Page: 1
Compilation date: 03/03/2015

Revision date: 04/02/2018

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CELLULOSE THINNERS

Product code: CELT

Synonyms: CELLULOSE THINNERS

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

 Classification under CLP:
 Carc. 2: H351; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Sens. 1: H317; STOT SE 3: H335

 Most important adverse effects:
 Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing cancer.

2.2. Label elements

Label elements:

| Hazard statements: | H225: Highly flammable liquid and vapour. |
|--------------------|--|
| | H317: May cause an allergic skin reaction. |
| | H318: Causes serious eye damage. |
| | H335: May cause respiratory irritation. |
| | H351: Suspected of causing cancer. |
| Hazard pictograms: | GHS02: Flame |
| | GHS05: Corrosion |

CELLULOSE THINNERS

Page: 2

GHS07: Exclamation mark

GHS08: Health hazard



Signal words: Danger

 Precautionary statements:
 P280: Wear protective gloves, protective clothing, eye protection and face protection.

 P303+361+353:
 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

 Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice/attention.

P310: Immediately call a POISON CENTER/doctor.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

MIBK

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|---|---------|
| 203-550-1 | 108-10-1 | - | Eye Irrit. 2: H319; STOT SE 3: H335; Flam. Liq. 2: H225; Acute Tox. 4: H332; | 44.250% |
| | | | -: EUH066 | |

2-BUTANONE OXIME

| 202-496-6 | 96-29-7 | - | Carc. 2: H351; Acute Tox. 4: H312; Eye | 40.000% |
|-----------|---------|---|--|---------|
| | | | Dam. 1: H318; Skin Sens. 1: H317 | |

ETHANOL

| 200-578-6 | 64-17-5 | Substance with a Community | Flam. Liq. 2: H225 | 10.280% |
|-----------|---------|----------------------------|--------------------|---------|
| | | workplace exposure limit. | | |

BUTAN-1-OL

| 200-751-6 | 71-36-3 | - | Flam. Liq. 3: H226; Acute Tox. 4: H302; | 4.450% |
|-----------|---------|---|---|--------|
| | | | STOT SE 3: H335; Skin Irrit. 2: H315; | |
| | | | Eye Dam. 1: H318; STOT SE 3: H336 | |

CELLULOSE THINNERS

Page: 3

| tion 4: First aid measures I.1. Description of first aid measures Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor. Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor. Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. Eye contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation of the throat. Inhalation: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation and special treatment needed Cotion 5: Fire-fighting measures Si.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. S.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and fash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. S.3. Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained | 200-659-6 67-56-1 | - Flam. Liq. 2: H225; Acute Tox. 3: H331; 0.430% Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370 | | |
|---|-------------------------------|--|--|--|
| Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of scap and water. Consult a doctor. Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor. Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. 8.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be can be expected after short-term exposure. 8.3. Indication of any immediate effects: Immediate effects: an be expected after short-term exposure. 8.4. Extinguishing media Extinguishing media: Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. | ction 4: First aid measur | es | | |
| immediately with plenty of soap and water. Consult a doctor. Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor. Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. 2.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation of the throat. Inhalation: There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects: Immediate effects can be expected after short-term exposure. 3.1. Indication of any immediate medical attention and special treatment needed 5.1. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. | .1. Description of first aid | neasures | | |
| Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor. Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. #2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 8.3. Indication of any immediate medical attention and special treatment needed Stin 5: Fire-fighting measures 8.1. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 8.2. Special hazards arising from the substance or mixture Exposure hazards: 8.3. Advice for fire-fighters Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive a | Skin contact | - | | |
| to drink immediately. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. I.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3.1. Indication of any immediate medical attention and special treatment needed 5.1. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. | Eye contact | | | |
| Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. I.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3.1. Indication of any immediate medical attention and special treatment needed 5.1. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | Ingestion | : Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water | | |
| becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. 2.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3.3. Indication of any immediate medical attention and special treatment needed stion 5: Fire-fighting measures 4.4. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 4.5. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 3.3. Advice for fire-fighters | | to drink immediately. | | |
| 3.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 8.3. Indication of any immediate medical attention and special treatment needed stion 5: Fire-fighting measures 6.1. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 6.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 6.3. Advice for fire-fighters | Inhalation | : Remove casualty from exposure ensuring one's own safety whilst doing so. If breathing | | |
| Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. I.3. Indication of any immediate medical attention and special treatment needed Scion 5: Fire-fighting measures Sci.1. Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. S.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. S.3. Advice for fire-fighters | | becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor. | | |
| Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3.3. Indication of any immediate medical attention and special treatment needed ction 5: Fire-fighting measures 3.1. Extinguishing media: Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 3.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. | I.2. Most important sympto | ms and effects, both acute and delayed | | |
| Eye contact: There may be irritation and redness. Ingestion: Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3. Indication of any immediate medical attention and special treatment needed ction 5: Fire-fighting measures 6.1. Extinguishing media: Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. | Skin contact | There may be irritation and redness at the site of contact. | | |
| vomiting. There may be irritation of the throat. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. A.3. Indication of any immediate medical attention and special treatment needed ettion 5: Fire-fighting measures 6.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 6.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 6.3. Advice for fire-fighters | Eye contact | There may be irritation and redness. | | |
| Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3.3. Indication of any immediate medical attention and special treatment needed 3.4. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 3.5. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 3.5. Advice for fire-fighters | Ingestion | : Severe poisoning can cause unconsciousness and severe and persistent nausea and | | |
| stomach pain may occur. There may be vomiting. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3.3. Indication of any immediate medical attention and special treatment needed 5.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | | vomiting. There may be irritation of the throat. | | |
| Delayed / immediate effects: Immediate effects can be expected after short-term exposure. 3. Indication of any immediate medical attention and special treatment needed ction 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | Inhalation | There may be irritation of the throat with a feeling of tightness in the chest. Nausea and | | |
| A.3. Indication of any immediate medical attention and special treatment needed ction 5: Fire-fighting measures A.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. A.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. Advice for fire-fighters | | stomach pain may occur. There may be vomiting. | | |
| Ction 5: Fire-fighting measures 5.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | Delayed / immediate effects | : Immediate effects can be expected after short-term exposure. | | |
| 5.1. Extinguishing media Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | 1.3. Indication of any immed | liate medical attention and special treatment needed | | |
| Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | ction 5: Fire-fighting mea | isures | | |
| 5.2. Special hazards arising from the substance or mixture Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. 5.3. Advice for fire-fighters | 5.1. Extinguishing media | | | |
| Exposure hazards: Highly flammable. Vapour may travel considerable distance to source of ignition and flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. | Extinguishing media | : Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Do not use water. | | |
| flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms explosive air-vapour mixture. | i.2. Special hazards arising | from the substance or mixture | | |
| explosive air-vapour mixture. | Exposure hazards | : Highly flammable. Vapour may travel considerable distance to source of ignition and | | |
| 5.3. Advice for fire-fighters | | flash back. In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Forms | | |
| | | explosive air-vapour mixture. | | |
| Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained | 5.3. Advice for fire-fighters | | | |
| | Advice for fire-fighters | : Wear protective clothing to prevent contact with skin and eves. Wear self-contained | | |
| breathing apparatus. | - | | | |

CELLULOSE THINNERS

6.1. Personal precautions, protective equipment and emergency procedures

 Personal precautions:
 Eliminate all sources of ignition. Refer to section 8 of SDS for personal protection

 details.
 Mechanically ventilate the spillage area whilst avoiding the formation of

 explosive concentrations - see section 9 of SDS.
 Mark out the contaminated area with

 signs and prevent access to unauthorised personnel.
 Do not attempt to take action

 without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements:Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.Earth any equipment used in handling. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep in cool, dry, ventilated storage and tightly closed containers. Keep away from direct sunlight. Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters.
 Suitable packaging: Glass. Coated steel. Do not use aluminium containers.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|-----------------|------------------|------------|--------------|
| UK | 208mg/m3, 50ppm | 416mg/m3, 100ppm | - | - |

Hazardous ingredients:

CELLULOSE THINNERS

Page: 5

Workplace exposure limits: Respirable dust 15 min. STEL 8 hour TWA 15 min. STEL State 8 hour TWA UK 1920 mg/m3 --**BUTAN-1-OL** UK 154 mg/m3 _ --METHANOL UK 266 mg/m3 333 mg/m3 --**DNEL/PNEC** Values DNEL / PNEC No data available. 8.2. Exposure controls Engineering measures: Ensure there is exhaust ventilation of the area. Ensure all engineering measures mentioned in section 7 of SDS are in place. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Hand protection: Nitrile gloves. Eye protection: Ensure eye bath is to hand. Safety glasses with side-shields. Skin protection: Protective clothing. PVC apron. Section 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties State: Liquid Colour: Clear. Odour: Pungent Evaporation rate: No data available. Oxidising: No data available. Solubility in water: Partially miscible. Also soluble in: Most organic solvents. Viscosity: Non-viscous Boiling point/range°C: 82 Melting point/range°C: No data available. Flammability limits %: lower: No data available. upper: No data available. Flash point°C: 2 Part.coeff. n-octanol/water: No data available. Autoflammability°C: No data available. Vapour pressure: No data available. Relative density: 0.810 @ 20 C pH: No data available. VOC q/I: 810

9.2. Other information

ETHANOL

Other information: No data available.

CELLULOSE THINNERS

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition. Flames. Moist air. Humidity.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-BUTANONE OXIME

| ORL | MUS | LD50 | 1 | gm/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 930 | mg/kg |
| SCU | RAT | LD50 | 2702 | mg/kg |

ETHANOL

| IVN | RAT | LD50 | 1440 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3450 | mg/kg |
| ORL | RAT | LD50 | 7060 | mg/kg |

BUTAN-1-OL

| IVN | RAT | LD50 | 310 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 2680 | mg/kg |
| ORL | RAT | LD50 | 790 | mg/kg |

METHANOL

| IVN RAT LD50 | 2131 | mg/kg |
|--------------|------|-------|
|--------------|------|-------|

CELLULOSE THINNERS

| ORL | MUS | LD50 | 7300 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 5628 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|--------------------------------|-------|-----------------------|
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| Respiratory/skin sensitisation | DRM | Hazardous: calculated |
| Carcinogenicity | | Hazardous: calculated |
| STOT-single exposure | INH | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

- **Ingestion:** Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting. There may be irritation of the throat.
- **Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting.
- Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Volatile. Absorbed only slowly into soil. Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

CELLULOSE THINNERS

Page: 8

| Section 14: Transport inform | ation |
|--------------------------------|---|
| 14.1. UN number | |
| UN number: | UN1263 |
| 14.2. UN proper shipping nar | ne |
| Shipping name: | Paint |
| 14.3. Transport hazard class | |
| Transport class: | |
| 14.4. Packing group | 5 |
| | |
| Packing group: | 1 |
| 14.5. Environmental hazards | |
| Environmentally hazardous: | No Marine pollutant: No |
| 14.6. Special precautions for | user |
| Section 15: Regulatory infor | nation |
| | |
| 15.1. Safety, health and envir | onmental regulations/legislation specific for the substance or mixture |
| 15.2. Chemical Safety Assess | sment |
| Chemical safety assessment: | Saftey Data Sheet complies with UK regulatory references in accordance with CHIP 3.1. |
| Section 16: Other informatio | n |
| Other information | |
| | |
| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No |
| | |
| | 2015/830. |
| Dhreese wood in a 2 and a 2. | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. H312: Harmful in contact with skin. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. H312: Harmful in contact with skin. H315: Causes skin irritation. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. H312: Harmful in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. H312: Harmful in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. H312: Harmful in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage. H319: Causes serious eye irritation. |
| Phrases used in s.2 and s.3: | * indicates text in the SDS which has changed since the last revision. EUH066: Repeated exposure may cause skin dryness or cracking. H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H301: Toxic if swallowed. H302: Harmful if swallowed. H311: Toxic in contact with skin. H312: Harmful in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage. |

CELLULOSE THINNERS

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.