

Expert finishes for wood and metal

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

March 2018

PRODUCT DATA SHEET

Product	Linseed Oil- Raw
Туре	Natural oil
Intended Use	Ideal for oiling cricket bats, adding to paint and softening metal glazing putty. Not suitable for oiling furniture or wooden floors. For furniture use Rustin's Danish Oil or Teak Oil . For floors use Rustin's Floor Oil .
Special Features	Natural product
Preparation	Ensure surface to be oiled is clean and dry.
Application	Apply with a rag or brush and wipe off excess with a dry rag or cloth.
Coats	As required.
Drying Time	Slow drying. Dependant on temperature, humidity and film thickness. For faster drying linseed oil use Rustin's Boiled Oil .
Re-coating Time	Recoat once oil has dried
Application Temp.	Ideally 15-25°C. Do not use below 15°C, or in conditions of high humidity.
Coverage	13-15 sq.m per litre, 1 coat, depending on the absorbency of the wood.
Maintenance	Re-oil periodically.
Compatibility	Compatible with most oil based products. Refer to manufacturer before mixing with other oils or varnishes.
Settlement	Stir before use.
Shelf- life/Storage	The shelf life of the product in an airtight container is a very long period of time. It is preferable to store the pro in a cool dry place.
Hazards	Low Hazard. See Health & Safety data sheets. Important: Rags used for oiling should be laid out flat to dry; otherwise they may catch fire due to spontaneous combustion
Clean-Up	Clean brushes with White Spirit or Rustin's Brush Cleaner.
Sizes	125ml 250ml 500ml 2lit 4lit 25lit