

WOOD DYE

Page: 1

Compilation date: 08/11/2017

Revision date: 23/02/2018

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WOOD DYE

Synonyms: WOOD DYE

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# **1.3. Details of the supplier of the safety data sheet**

Company name: Rustins Ltd

Waterloo Road

Cricklewood

London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

# 1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315

**Most important adverse effects:** Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

# 2.2. Label elements

#### Label elements:

Hazard statements:	H226: Flammable liquid and vapour.	
	H315: Causes skin irritation.	
	H319: Causes serious eye irritation.	
	H336: May cause drowsiness or dizziness.	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	



# WOOD DYE

Signal words:WarningPrecautionary statements:P280: Wear eye protection.P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.<br/>Rinse skin with water.P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br/>P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove<br/>contact lenses, if present and easy to do. Continue rinsing.<br/>P312: Call a POISON CENTER/doctor if you feel unwell.<br/>P370+378: In case of fire: Use carbon dioxide to extinguish.

2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

3.2. Mixtures

## Hazardous ingredients:

3-BUTOXYPROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-878-4	5131-66-8	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	20.950%

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	0.751%
			Eye Irrit. 2: H319; STOT SE 3: H335;	
			Skin Irrit. 2: H315; Aquatic Chronic 2:	
			H411	

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226;	0.501%
			STOT SE 3: H335; Aquatic Chronic 2: H411	

# MESITYLENE

203-604-4	108-67-8	-	Flam. Liq. 3: H226; STOT SE 3: H335;	0.125%	
			Aquatic Chronic 2: H411		

# Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

Page: 2

# WOOD DYE

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

**Ingestion:** There may be vomiting and diarrhoea. There may be shortness of breath due to congestion of the lungs.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol resistant foam. Do not use water.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Flammable.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

# Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a suitable container.

## 6.4. Reference to other sections

## Section 7: Handling and storage

## 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Earth any equipment used in handling. Use non-sparking tools.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep away from direct sunlight. Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

# WOOD DYE

Page: 4

-

## 7.3. Specific end use(s)

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

## Hazardous ingredients:

# 1,2,4-TRIMETHYLBENZENE

Workplace exposure limits:		Respirable dust		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	125 mg/m3	-	-	-
MESITYLENE				

-

-

UK

**DNEL/PNEC** Values

DNEL / PNEC No data available.

25 ppm

8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Colour Range	
Odour:	Paraffinic.	
Evaporation rate:	No data available.	
Oxidising:	No data available.	
Solubility in water:	Not miscible	
Also soluble in:	Benzene.	
Viscosity:	Non-viscous	
Boiling point/range°C:	150-190 Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available. upper:	No data available.
Flash point°C:	38 Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available. Vapour pressure:	No data available.
Relative density:	0.850 @ 20 C pH:	No data available.
VOC g/l:	No data available.	

# WOOD DYE

**Page:** 5

# 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

# 10.4. Conditions to avoid

Conditions to avoid: Sources of ignition. Direct sunlight. Heat.

# 10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

# **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

# Section 11: Toxicological information

# 11.1. Information on toxicological effects

## Hazardous ingredients:

## 3-BUTOXYPROPAN-2-OL

SKN RBT LD50	3100	mg/kg
--------------	------	-------

#### 1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

## LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL RAT LD50 8400 mg/kg	
-------------------------	--

# MESITYLENE

IPR GPG	LDLO	1303	mg/kg
---------	------	------	-------

WOOD DYE

#### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

- **Ingestion:** There may be vomiting and diarrhoea. There may be shortness of breath due to congestion of the lungs.
- **Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

## 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: No data available.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

## Section 13: Disposal considerations

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# WOOD DYE

Page: 7

# Section 14: Transport information

14.1. UN number

UN number: UN1263

## 14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

# Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

Chemical safety assessment: Saftey Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Marine pollutant: Yes

# Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H332: Harmful if inhaled.
	H335: May cause respiratory irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product. As the specific
	conditions of use of the product are outside the supplier's control, the user is
	responsible for ensuring that the requirements of relevant legislation are complied with.