



March 2018

## PRODUCT DATA SHEET

<b>Product</b>	<b>Wudfil Easy Stain Wood Repair Filler</b>
<b>Type</b>	A two part wood filler. Provides a strong long lasting repair for all interior and exterior wood work. Available in Mahogany, Pine, Teak, Oak, Cream and White colour.
<b>Intended Use</b>	For all types of interior and exterior timber.
<b>Special Features</b>	The filler hardens within 10 mins at ambient temperature. It can be sanded, drilled, machined and planed and is particularly useful for carrying out repairs to edges on joinery where high strength is needed. Specially formulated to facilitate uptake of wood stains after sanding.
<b>Preparation</b>	The surface must be clean, dry and free from all traces of oil, grease and dust. To provide good adhesion to timber, key the surface by lightly sanding with a medium grade of sand paper.
<b>Application</b>	Mix the filler with the hardener on a non-porous surface using an amount of filler the size of a golf ball to a pea-sized ball of hardener as the mixing ratio. Mix until an even colour is obtained. Do not prepare more than is required as any excess will be unusable within 10 mins. Using a putty knife or similar apply sufficient filler so that it is proud of the surface to allow a continuous smooth surface to be obtained by sanding.
<b>Coats</b>	Single application should be sufficient.
<b>Drying Time</b>	Approx. 10 minutes depending on temperature and humidity.
<b>Re-coating Time</b>	Once fully cured and after sanding back, most wood stains, varnishes and paints can be applied
<b>Application Temp.</b>	Ideally 15-25°C, but do not use below 10°C.
<b>Coverage</b>	N/A
<b>Maintenance</b>	N/A
<b>Compatibility</b>	Compatible under most finishes. For best results sand before staining and finishing.
<b>Settlement</b>	N/A
<b>Shelf-life/Storage</b>	12 months if stored in cool and dry place below 25 deg C in original, sealed packaging...
<b>Hazards</b>	Harmful by inhalation. Contains Styrene. Do not breathe vapours. Wear suitable protective gloves and eye/face protection. A full Health and Safety Data Sheet is available on request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	All tools must be cleaned immediately after use with <b>Rustins Cellulose Thinners</b> before product sets hard
<b>Sizes</b>	