

# Teak Oil

## Product Information Sheet

### Description

Bartoline Teak Oil is suitable for replacing the natural sheen that wood can lose after long periods drying in the sun. This is a popular wood treatment to replace natural oils removed by weathering. Bartoline Teak Oil can be used internally or externally on unpolished wood surfaces and is especially suited for use on wooden garden furniture. Bartoline Teak Oil contains a solvent carrier to aid penetration of the oil into hardwoods such as Oak and Teak.

### Preparation

Ensure that the surface to be treated is thoroughly clean and dry. Apply Teak Oil liberally by either brushing or using a cloth. Remove excess Teak oil with a dry clean cloth after saturation. Drying time is approximately 14 hours however this will vary depending upon thickness of coating applied and local climatic conditions.

### Health & Safety

See MSDS for full information.

Caution – Do not leave soiled application cloths where they may constitute a fire hazard, as they may be liable to spontaneous combustion. Ideally soiled cloths should be immediately burnt; if this is not possible they should be washed in soapy water and hung outside to dry.

### Technical Data

<b>Physical State:</b>	<b>Liquid</b>
<b>Colour</b>	<b>Brown</b>
<b>Flash Point Deg C</b>	<b>41</b>
<b>Non volatile content</b>	<b>24 – 26%</b>
<b>Viscosity @ 20 Deg C (B2 Flow Cup)</b>	<b>32 - 37 Seconds</b>
<b>Auto ignition Temperature Deg C</b>	<b>450 solvent fraction</b>
<b>Specific gravity at 20 deg C</b>	<b>0.820 ± 0.01</b>
<b>Voc Content</b>	<b>700g/l</b>

### Packing Specification

<b>Product / Pack Size</b>	<b>Quantity Per Carton</b>	<b>Cartons / Drums Per Pallet.</b>
250 ml PET Bottles	12	174
500 ml PET Bottles	6	144
500ml PET Trigger Spray	6	124
1 Litre PET Flasks	6	81
2 Litre PET Bottles	8	44
5 Litre Poly Bottles	4	40
20 Litre Drums	0	42
205 Litre Drums	0	4

**Customs Tariff Code**

3210 0090

**Shipping Classification**

<b>Correct Shipping Name:</b>	Paint (White Spirit)
<b>Classification:</b>	Class 3
<b>UN Number:</b>	UN 1263
<b>Packing Group:</b>	III
<b>Flash Point:</b>	41 Degrees Celsius

**Additional Information:** Marine Pollutant